#### **PCT**

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5: (11) International Publication Number: WO 94/04643 A1 C11D 1/62, 3/02, 3/20 (43) International Publication Date: 3 March 1994 (03.03.94) (21) International Application Number: PCT/US93/07607 (74) Agent: LIEBERMAN, Bernard; Colgate-Palmolive Company, 909 River Road, Piscataway, NJ 08855-1343 (US). (22) International Filing Date: 17 August 1993 (17.08.93) (81) Designated States: HU, European patent (AT, BE, CH, (30) Priority data: DĔ, DK, ES, FR, GB, GR, IE, ÎT, LU, MĆ, NĹ, PT, 07/934,100 21 August 1992 (21.08.92) US 08/086,809 2 July 1993 (02.07.93) US

(71) Applicant: COLGATE-PALMOLIVE COMPANY [US/US]; 300 Park Avenue, New York, NY 10022 (US).

(72) Inventors: GRANDMAIRE, Jean-Paul; Rue Sous le Château 45, B-4821 Andrimont (BE). TACK, Viviane; Rue Baudrihaye 17, B-4630 Soumagne (BE). JACQUES, Alain; Rue de l'Institut 202, B-4570 Blegny (BE). HARMALKER, Subhash; 11 Gifford Road, Somerset, NJ 08873 (US).

**Published** 

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: RINSE CYCLE FABRIC SOFTENER

$$\begin{array}{c|c}
 & O & + \\
 & |CH_2|_nOCR & \\
 & |O| & |CH_2|_mOCR \\
 & |R_3 - N| - |CH_2|_mOCR & X^{-1} \\
 & |R_2| & |CH_2|_mOCR & X^{-1}
\end{array}$$

#### (57) Abstract

An environmentally compatible and biodegradable rinse cycle fabric conditioning composition is provided capable of providing improved softening with significant reduction and solubilization of unwanted mineral encrustations on fabrics to be softened. The composition comprises: (a) from about 1 to about 20 %, by weight, of a diesterified long chain fatty acid cationic fabric softener represented by general formula (I), wherein RCO represents the residue of a fatty acid having from about 12 to 24 carbon atoms; R<sub>2</sub> and R<sub>3</sub> represent independently a lower alkyl group or a hydroxyalkyl group having 1 to 4 carbon atoms; n and m are integers from 1 to 4 and X is a water-solubilizing anion; and (b) from about 1 to about 25 %, by weight, of unreacted organic or mineral acid.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	iE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic	RU	Russian Federation
CF	Central African Republic		of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	Si	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovak Republic
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LŸ	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	ÜÄ	Ukraine
DE	Germany	MG	Madagascar	US	United States of America
DK	Denmark	ML	Mali	ÜZ	Uzbekistan
ES	Spain	MN	Mongolia	٧Ñ	Vict Nam
FI	Finland			***	7 104 1 10111

#### RINSE CYCLE FABRIC SOFTENER

#### BACKGROUND OF THE INVENTION

5

10

15

20

25

30

35

This invention relates to fabric softening compositions which are suitable for softening-in-the-rinse-cycle-of-an-automatic-household-washing-machine, and which are especially adapted for use under European laundering conditions. More particularly, the present invention relates to fabric conditioning compositions comprising a diesterified quaternary ammonium salt in combination with an acid and optionally a fatty alcohol, which compositions are characterized by superior environmental compatibility relative to conventional quaternary ammonium fabric softening compositions concomitant with providing improved calcium salt solubilization and reduction of encrustation on treated fabrics.

Esterified quaternary ammonium salts are known in the art as fabric softeners, and are generally recommended for use in combination with fatty alcohols or linear alkyoxylated alcohols. U.S. Patent 4,844,823 to Jacques et al describes a diesterified long chain fatty acid di lower-alkyl quaternary ammonium salt as a preferred class of cationic fabric softeners for use in conjunction with a fatty alcohol having from 10 to 24 carbon atoms. In EP-A-309,052 there is disclosed a liquid softening composition containing a monoester or diester quaternary ammonium compound in combination with an alkyoxylated alcohol which is said to reduce the ester hydrolysis rate of the quaternized softening compound, thereby improving its chemical stability.

The combination of organic acid with cationic fabric softener is also disclosed in the prior art. U.S. Patent 3,904,359 and 3,954,630 to Ramachandran disclose a fabric treating composition comprising a complexing acid such as citric or maleic acid in combination with a quaternary ammonium softening compound. The function of the acid, as stated in the patent, is to prevent yellowing of fabrics due to build-up of cationic softener and to provide a complexing site for metal ions contained in soils. U.S. Patent 4,162,984 describes a mixture of a quaternary ammonium salt and an aromatic carboxylic acid such as benzoic acid to provide an emulsion having significantly increased viscosity. U.S. Patent 4,426,299 discloses a fabric softening composition comprising a defined quaternary ammonium compound and a viscosity control agent which may be a C<sub>9</sub>-C<sub>24</sub> fatty acid. In U.S. Patent 4,559,151 there is disclosed the combination of quaternary ammonium salts with a lactic acid salt for the purpose of imparting improved antistatic properties. U.S. Patent 4,832,856 discloses mixtures of carboxylic acids with defined amines and/or quaternary ammonium

PCT/US93/07607

5

10

15

20

25

30

compounds, the resulting mixture being said to provide softening using inexpensive raw materials. EP 404,471 relates to an isotropic liquid fabric softener comprising at least 20% of a fabric softening material and at least 5% of an organic acid, the isotropic compositions being said to be more stable than lamellar structures. DE 3,312,328 (Benkiser) similarly describes a composition containing a fabric softener material and an organic acid. The addition of acid serves to complex alkaline earth and heavy metal ions.

Although satisfactory results may be obtained with one or more of these prior art fabric softening compositions, further improvements are needed in terms of being able to provide efficacious fabric softening with a biodegradable cationic fabric softening compound, concomitant with the ability to substantially solubilize and remove mineral encrustation from the fabrics to be treated. This is a particularly important need for European fabric conditioning compositions where the cumulative deposition of mineral salts on fabrics during repetitive laundering in hard water is an acute problem. Moreover, the increased emphasis in Europe on using biodegradable softening compounds which have no toxic effect on aquatic organisms in aqueous effluent streams makes it imperative that conventional softening compounds, notably, the di-long chain, di-short chain quaternary ammonium compounds be replaced as the softening compounds of choice in commercial rinse-cycle softening compositions with softening compounds which are significantly more compatible with environmental concerns.

#### SUMMARY OF THE INVENTION

The present invention provides environmentally compatible and biodegradable rinse cycle fabric conditioning compositions capable of providing improved softening with significant reduction and solubilization of unwanted mineral encrustations on fabrics to be softened, such encrustations having been generally deposited on the fabrics during the course of prior laundering in water having a high mineral content, which comprises:

(a) from about 1 to about 20%, by weight, of a diesterified long chain fatty acid cationic fabric softener represented by the general formula

35 
$$\begin{bmatrix} (CH_{2})_{n}OCR \\ I & O \\ I & O \\ I & I \\ R_{3} - N - (CH_{2})_{m}OCR \\ R_{2} \end{bmatrix}$$
 X-

10

15

20

25

30

35

wherein RCO represents the residue of a fatty acid having from about 12 to 24 carbon atoms;
R<sub>2</sub> and R<sub>3</sub> represent independently a lower alkyl group or a hydroxyalkyl group having 1 to 4 carbon atoms;
n and m are integers from 1 to 4 and X is a water-solubilizing anion; and

(b) from about 1 to about 25%, by weight, of unreacted organic or mineral

In a preferred embodiment of the invention, the fabric softening composition further contains from about 0.2 to about 5%, by weight, preferably from about 0.5 to about 3%, and most preferably from about 0.5 to 1%, by weight, of a fatty alcohol having from about 10 to about 24 carbon atoms.

In another preferred embodiment of the invention the cationic fabric softener is a triethanolamine diester which comprises N-methyl, N, N-di (beta  $\rm C_{14}$ - $\rm C_{18}$  acyloxy-ethyl), N-beta hydroxy ethyl ammonium, and the anion is halide, methylsulfate or ethylsulfate.

The invention also encompasses a method for softening fabrics and removing unwanted mineral encrustations therefrom comprising rinsing the fabrics to be treated in an aqueous bath containing an effective amount of a composition comprised of the above-defined fabric softening composition.

The present invention is predicated on the discovery that the combination of cationic fabric softener as defined above with an organic or mineral acid provides a biodegradable softener which has the capability of removing mineral encrustations such as calcium and magnesium salts, and in particular, phosphates and carbonates of calcium and magnesium, which cumulatively deposit on the fabrics during the course of prior laundering in hard water, i.e. water having a mineral content above about

300 ppm, conditions generally associated with European laundering conditions.

A particularly preferred softening compound as described herein comprises di(stearoyl-oxyethyl-) methyl-hydroxyethyl ammonium, and X is a halide, methosulfate or ethylsulfate.

#### **DETAILED DESCRIPTION OF THE INVENTION**

The compositions of the present invention are environmentally compatible and biodegradable rinse cycle fabric conditioning compositions which contain as the active fabric softening compound a diesterified long chain fatty acid cationic fabric softener as defined above. The use of such fabric softening compound avoids the more traditional di-long chain, di-short chain quaternary ammonium softeners which are used extensively in commercial rinse cycle softeners, but which presently have

20

25

30

35

become the focus of increasing legislative concerns, particularly in Europe, because of their lack of biodegradability in aqueous effluent streams.

A preferred "diesterified quat" in accordance with the invention is commercially available from, for instance, Stepan Chemical Co. under the Stepantex trademark, such as Stepantex VHR90 which has the formula

where R is hydrogenated or non-hydrogenated tallow and X may be chloride or sulfate.

The total amount of diesterified cationic fabric softener in the total composition is from about 1 to 20%, by weight, preferably from about 2 to 10%, by weight.

The second essential ingredient of the fabric conditioning composition is the acid which has a dual function, depending on the acid concentration. The first function is preventive in nature and occurs when the acid in the diluted rinse cycle solution is present in sufficient amount to react with the insoluble salts of the water hardness ions (calcium and magnesium) to form soluble acid salts and to remove any mineral salts which may have deposited on fabrics during the washing step of the wash cycle. The second function is more curative in nature and refers to the removal of mineral encrustations which have been cumulatively deposited during prior washing throughout the fabric's life.

To effect the aforementioned preventive function, an acid concentration of from about 1 to about 8%, by weight, preferably from about 5 to about 8%, is required in the fabric softening composition depending on the dosage used and the hardness of the water. For European washing machines containing about 20 to 25 liters of water, for example, a dosage of 110 to 150 ml of softening composition is typical for use in the rinse cycle; the water hardness varies from about 200 to 400 ppm, most typically about 300 ppm. To effect the curative function of the acid for removal of previously deposited mineral encrustations, an acid concentration of from about 5 to about 25%, by weight, preferably from about 8 to 25%, by weight, is required in the fabric softening composition.

The acid used may be an organic or mineral acid. The organic acids are preferably saturated or unsaturated  $C_2$ - $C_6$  carboxylic acids such as citric acid, formic acid, maleic acid, tartaric acid and succinic acid. Citric acid, malonic acid and maleic acid are particularly preferred. A mineral acid, such as HCI, may be used

10

advantageously in combination with such organic acid, the amount of acid used in excess of protonation being referred to herein as "excess".

An optional fabric conditioning ingredient is a fatty alcohol wherein the hydrophobic group may be a straight or branched chain alkyl or alkenyl group having from about 10 to 24, preferably from about 10 to 20, especially preferably from about 12 to 20 carbon atoms. Specific examples of the fatty alcohol include decanol, dodecanol, tetradecanol, pentadecanol, hexadecanol, octadecanol, lauryl alcohol, palmityl alcohol, stearyl alcohol, oleyl alcohol, and mixtures thereof. Furthermore, the fatty alcohol may be of natural or synthetic origin and my include, for example, mixed alcohol, such as C<sub>16</sub>-C<sub>18</sub> alcohols prepared by Ziegler polymerization of ethylene.

The fatty alcohol may be present in the composition in a minor amount relative to the cationic fabric softener such that the ratio, by weight, of the cationic fabric softener to fatty alcohol is in the range of from about 6:1 to 2:1, preferably about 5:1 to 3:1, and most preferably about 4:1.

## **EXAMPLE 1**

Compositions A and B in accordance with the invention were prepared as described below, and compared to the Reference Composition which is in accordance with the prior art.

5

5				
	Composition A	Weight %		
10	N, N-Di(stearoyl-oxyethyl) ester, N-methyl, N-ethanol ammonium chloric	de 5.5		
10	Synperonic A 20 <sup>(1)</sup> (emulsifier)	0.3		
	Citric Acid	10.0		
15	Perfume	0.3		
	Preservative and colorant	less than 0.1		
20	Water	balance		
25	A nonionic surfactant comprised of C <sub>13</sub> -15 alcohol ethoxylate having 20 moles EO/mole alcohol.			
	Composition B	Weight %		
30	N, N-Di(stearoyl-oxyethyl) ester, N-methyl, N-ethanol ammonium chlorid	le <b>3.</b> 3		
•	Fatty alcohol (C <sub>16</sub> -18 alcohol)	0.83		
35	Synperonic A 20 (emulsifier)	0.3		
33	Citric acid	10.0		
	Perfume	0.3		
40	Preservative and colorant	less than 0.1		
	Water	Balance		

20

25

30

	Water	Balance	
10	Sodium chloride	less than 0.1	And the second s
	Preservative and colorant	less than 0.1	
<b>,</b>	Perfume	0.3	
5	Ditallow dimethyl ammonium chloride	5.0	
	Reference Composition	Weight %	

Each of softening compositions A, B and the Reference Composition were added to the rinse cycle of a European washing machine having 25 liters of water in a dosage of 4.4 grams per liter of water and containing previously encrusted towels containing 24%, by weight, encrustation. The softening performance of each composition was evaluated by a three member panel. All three softening compositions were graded by the panel as providing the same softening performance.

The percent of encrustation solubilization on the encrusted fabrics was measured for all three of the tested compositions. The encrustation level was measured by calcination of the encrusted fabrics whereby weight measurements were taken before and after calcination of the fabric in an oven at 800°C for 1 hour. After calcination, the organic materials such as the fibers and detergents are burned in the oven with only the minerals remaining; the latter being primarily calcium phosphate salts, i.e. encrustations.

The encrustation solubilization, expressed as a percentage, refers to the amount of encrustation removed during the rinse cycle treatment relative to the amount of encrustation present originally. For Compositions A and B the percent of encrustation solubilization was 2.3%; for the Reference composition, less than 0.1% of encrustation was solubilized.

#### **CLAIMS**

- 1. An environmentally compatible and biodegradable rinse cycle fabric conditioning composition capable of providing improved softening with significant reduction and solubilization of unwanted mineral encrustations on fabrics to be softened, such encrustations having been generally deposited on the fabrics during the course of prior laundering in water having a high mineral content, which comprises:
  - (a) from about 1 to about 20%, by weight, of a diesterified long chain fatty acid cationic fabric softener represented by the general formula

20

5

10

wherein RCO represents the residue of a fatty acid having from about 12 to 24 carbon atoms;

R<sub>2</sub> and R<sub>3</sub> represent independently a lower alkyl group or a hydroxyalkyl group having 1 to 4 carbon atoms;

25

40

- n and m are integers from 1 to 4 and X is a water-solubilizing anion; and (b) from about 1 to about 25%, by weight, of unreacted organic or mineral acid.
- 2. A fabric conditioning composition according to claim 1 wherein said cationic fabric softener is a triethanolamine diester which comprises N-methyl, N, N-di (beta C<sub>14</sub>-C<sub>18</sub> acyloxy-ethyl), N-beta hydroxy ethyl ammonium, and wherein X is a halide, methylsulfate, or ethylsulfate.
  - 3. A fabric conditioning composition according to claim 1 wherein said cationic fabric softener comprises di (stearoyl-oxyethyl) methyl-hydroxyethyl ammonium and X is a halide, methylsulfate or ethylsulfate.
- A fabric conditioning composition according to claim 1 which further includes from about 0.2 to about 5%, by weight, of a fatty alcohol having from about 10 to about 24 carbon atoms.
  - 5. A fabric conditioning composition according to claim 1 wherein the concentration of acid is from about 8 to 25%, by weight, of the fabric conditioning composition.

- 6. A fabric conditioning composition according to claim 1 wherein the acid is citric acid.
- 7. A fabric condition composition according to claim 1 wherein the acid is malonic or maleic acid.
- 5 8. A fabric conditioning composition according to claim 4 wherein the fatty alcoholis a C<sub>16</sub>-C<sub>18</sub> alcohol.
  - 9. A method for softening fabrics and removing unwanted mineral encrustation therefrom comprising rinsing the fabrics to be treated in an aqueous bath containing an effective amount of a rinse cycle fabric conditioning composition comprising
    - (a) from about 1 to about 20%, by weight, of a diesterified long chain fatty acid cationic fabric softener represented by the general formula

15 
$$\begin{bmatrix} O \\ | | \\ (CH_2)_nOCR \\ | O \\ | | \\ R_3 - N - (CR_2)_mOCR \end{bmatrix}$$
 X-

wherein RCO represents the residue of a fatty acid having from about 12 to 24 carbon atoms;

- 25 R<sub>2</sub> and R<sub>3</sub> represent independently a lower alkyl group or a hydroxyalkyl group having 1 to 4 carbon atoms; n and m are integers from 1 to 4 and X is a water-solubilizing anion; and
  - (b) from about 1 to about 25%, by weight, of unreacted organic or mineral acid.
- The method of claim 9 wherein said cationic fabric softener comprises N-methyl, N, N-di(beta C<sub>14</sub>C<sub>18</sub> acyloxy-ethyl), N-beta hydroxy ethyl ammonium, and wherein X is a halide, methylsulfate, or ethylsulfate.
  - 11. The method of claim 9 wherein the concentration of acid is from about 8 to 25%, by weight, of the fabric conditioning composition.
- 35 12. The method of claim 9 wherein the acid is citric acid.
  - 13. The method of claim 9 wherein the acid is malonic acid or maleic acid.

International Application No
PCT/US 93/07607

		PCI/	US 93/0/60/
A. CLASS IPC 5	SIFICATION OF SUBJECT MATTER C11D1/62 C11D3/02 C11D	3/20	
According	to International Patent Classification (IPC) or to both nationa	l classification and IPC	· · · · · · · · · · · · · · · · · · ·
	S SEARCHED		
Minimum (	documentation searched (classification system followed by cla C11D	ssification symbols)	
Documenta	ation searched other than minimum documentation to the exten	it that such documents are included in th	e fields searched
-			,
Electronic (	data base consulted during the international search (name of d	ata base and, where practical, search terr	ns used)
	MENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of	the relevant passages	Relevant to claim No.
X	EP,A,O 404 471 (UNILEVER) 27 ! 1990	December	1-6,8-12
	cited in the application see the whole document		
(	EP,A,O 345 495 (HENKEL KGAA.) 13 December 1989		1,6,9,12
	see page 2, line 39 - line 54; examples 3-5	; Claims 1-7;	
١	EP,A,O 423 894 (COLGATE - PALM 24 April 1991 see the whole document	1	
		-/	
X Furt	her documents are listed in the continuation of box C.	X Patent family members ar	e listed in annex.
Special car	tegories of cited documents:	"T" later document published after	
conside	ent defining the general state of the art which is not ered to be of particular relevance	cited to understand the princi- invention	nflict with the application but ple or theory underlying the
filing	document but published on or after the international date ent which may throw doubts on priority claim(s) or	"X" document of particular relevant cannot be considered novel of involve an inventive step who	
which citation	is cited to establish the publication date of another n or other special reason (as specified)	"Y" document of particular releva- cannot be considered to invol	nce; the claimed invention ve an inventive step when the
other r	ent referring to an oral disclosure, use, exhibition or neans ent published prior to the international filing date but	document is combined with o ments, such combination bein in the art.	ng obvious to a person skilled
later th	nan the priority date claimed actual completion of the international search	'&' document member of the sam  Date of mailing of the internal	
	February 1994	15.02.9	1
lame and n	nailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016	Serbetsoglou,	A

Form PCT/ISA/210 (second sheet) (July 1992)

1

International Application No
PCT/US 93/07607

_			PCT/US 93/0/607
<u></u>		ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Ca	ategory *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A		EP,A,O 309 052 (THE PROCTER & GAMBLE CO.) 29 March 1989	1,9
	-	cited in the application see page 5, line 1 - page 6, line 5;	
		claims; examples—III,IV————————————————————————————————	
A	se 14 - 144 - 144 - 1	DE,A,33 12 328 (J.A.BENCKISER GMBH.) 11 October 1984	1,5-7,9, 11-13
		-cited in the application	
A		EP,A,O 239 910 (THE PROCTER & GAMBLE CO.)	1
		7 October 1987 see page 7, paragraph 1 -paragraph 4; claim 1	
A		EP,A,O 086 423 (HENKEL KGAA.) 24 August	1,6
		1983 see page 5, line 24 - page 6, line 15; claims 1,2	
A		EP,A,O 486 113 (AKZO N.V.) 20 May 1992 see column 3, line 11 - line 55; claims 1-10	1,6
A		GB,A,2 170 829 (COLGATE - PALMOLIVE CO.) 13 August 1986 cited in the application see claim 1	1,4,8
<b>.</b>			
			·
	Ì		
•			
,			
			}
, 1			
•			
	ł		
			·
			]
	- 1		ì

information on patent family members

Internacional Application No PCT/US 93/07607

Patent document cited in search report	Publication date	Patent : memb		Publication date
EP-A-0404471	27-12-90	AU-B-	623019	30-04-92 20-12-90
		AU-A- JP-A-	5711990 3027180	05-02-91
EP-A-0345495	13-12-89	DE-A-	3818013	30-11-89
		WO-A- EP-A,B	8911527 0418273	30=11=89 27=03=91
		LF A, D		
EP-A-0423894	24-04-91	AU-B-	638058 6374190	17-06-93 18-04-91
		CA-4-	2027644	17-04-91
		JP-A-	3185182	13-08-91
		US-A-	5133885	28-07-92
EP-A-0309052	29-03-89	AU-A-	2243488	23-03-89
		DE-A-	3876196	07-01-93 15-07-93
		FI-B- JP-A-	89605 1162872	27-06-89
DE-A-3312328	 11-10-84	NONE		
		GB-A-	2188653	07-10-87
EP-A-0239910	07-10-87	AU-B-	599966	02-08-90
		AU-A-	7096587	08-10-87
		CA-A-	1279448	29-01-91 12-11-92
		DE-A- JP-A-	3782075 63006168	12-11-92
		US-A-	4767547	30-08-88
EP-A-0086423	24-08-83	DE-A-	3205317	25-08-83
		DE-A-	3374693 	07-01-88
EP-A-0486113	20-05-92	JP-A-	4289271	14-10-92
GB-A-2170829	13-08-86	US-A-	4772403	20-09-88
		AT-B-	395614 5256586	25-02-93 07-08-86
		AU-A- AU-B-	5256586 627877	07-08-86
				30-08-90
		AU-A-	5501490	20-00-30

information on patent family members

Internavokal Application No
PCT/US 93/07607

Patent document Publication cited in search report date	Patent family member(s)	Publication date	
GB-A-2170829	CH-A- 671581	15-09-89	
	DE-A- 3602089	21-08-86	1
	FR-A- 2576614	01-08-86	!
	GB-A,B 2207154	25-01-89	
	GB-A,B 2207446	01-02-89	1
	JP-A- 61179372	12-08-86	. 4.
	LU-A- 86276	04-08-86	
	NL-A- 8600219	18-08-86	
	SE-A- 8600364	31-07-86	,
and the state of t	US-A- 4844823	04-07-89	1 1977 198 1987 197 178 478 488

Form PCT/ISA/210 (patent family annex) (July 1992)

THIS PAGE BLANK (USPTO)

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

# IMAGES ARE BEST AVAILABLE COPY.

□ OTHER: \_\_\_\_\_

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)